



## ILA-USMX JOINT SAFETY COMMITTEE

OSH Circular 2020-04 (15 April 2020)

### “Jostling” Accidents on the Rise



Intermodal chassis, bomb carts and tractors were not designed with their lifting in mind.

When they “go up” with the load, something is generally wrong and instantaneous attention/correction must occur. Any policy and/or procedure that achieves that end will be considered suitable.

In container lifting operations, it is generally considered a good practice to “**float the load.**” In sum, the lifting appliance (crane/industrial truck) operator should first ensure that only the container is being lifted by raising the load a very small distance first and then hoisting once it is assured that only the container (and not the chassis/bomb cart/tractor) is being lifted.

Given the number and critical nature of such accidents that have occurred recently, and the undeniable potentials that exist going forward, operations that do not “float the load” on each and every lift will be walking a very thin line in terms of ensuring the safety of their work.

Got an OSH-related question? Write to the JSC at: [blueoceana@optonline.net](mailto:blueoceana@optonline.net)

### Working Together For The Benefit Of All

ILA-USMX OSH Circulars are devised to reflect the best possible information and guidance, and are products of diligent research and the most up to date subject matter knowledge. Consequently, while the information contained herein is believed to be accurate, owing to a host of factors ILA-USMX can convey no direct or implied warranty relative to the reliance of parties upon content.